



PNEUMATIC PLANTER

- Usually it is more appropriate to use where there is plenty of straw waste on the field.
- For disc type machines, fertilizer coulters are also produced with double-discs.
- Depth settings can be adjusted with the help of the wheels next to the planter disc, while pressure is applied with V-shaped pressure wheels at the rear of the unit. Also optionally a seed pressure wheel is attached to rear side of the planter discs for small and delicate seeds.





MODELS	Eldorada D-4 (disc coulters)	Eldorada D-6 (disc coulters)	Eldorada D-8 (disc coulters)	Eldorada 4 (tyne coulters)	Eldorada 6 (tyne coulters)	Eldorada 8 (tyne coulters)
Chassis width, m	3	4,5	6	3	4,5	6
Number of planting units	4	6	8	4	6	8
Interrow distance, cm	70	70	70	70	70	70
Seed hoppers capacity, lt	4x42	6x42	8x42	4x42	6x42	8x42
Press wheels	V-shaped press wheels, 325x50 mm	V-shaped press wheels, 325x50 mm	V-shaped press wheels, 325x50 mm	Big-diameter press wheels	Big-diameter press wheels	Big-diameter press wheels
Drive wheels	2 wheels	2 wheels	4 wheels	2 wheels	2 wheels	4 wheels
Hydraulic markers	+	+	+	+	+	+
Extra press wheel in the row	+	+	+	-	-	-
Transport system	-	-	option	-	-	option
PTO drive transmission	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Capacity, ha/h	2,8	4,2	5,6	2,8	4,2	5,6
Fertiliser hoppers capacity, lt	2x200 (disc coulters for fertilisers)	2x300 (disc coulters for fertilisers)	4x220 (disc coulters for fertilisers)	2x200 (tyne coulters for fertilisers)	2x300 (tyne coulters for fertilisers)	4x220 (tyne coulters for fertilisers)
Seeding control system	+	+	+	+	+	+
Maximum working speed, km/h	5-7	10-12	10-12	5-7	10-12	10-12
Weight, kg	1180	1700	2300	950	1200	1900
Power required, h.p.	70+	80-100	120-150	70+	80-100	120-150

ALMEKS

ALMEKS DIŐ TİCARET LTD. ŐTİ.

Kıbrıs Őhitleri Caddesi No: 98/11 Alsancak - İZMİR / TÜRKİYE

+90(232) 463 7044

+90(232) 463 9433

almeks.com.tr

info@almeks.com.tr

/almeks

YouTube /almeks

Download on the
App Store

Google play